

Duron Paint Internal and External

Duron high-quality paints are highly resistant and durable on walls and less likely to show brush mark flaws thus providing a better finish. Duron external paint has a high level of UV protection and carries a very good shielding reputation against harsh winters, strong winds, storms and heavy rain.



Internal Paint application



Duron Acrylic hardtex internal paint can be specifically used on all kind of surfaces and masonry buildings. Internal Duron paint can be also used on internal woodwork for its excellent smooth finish. Duron paint can help against mould problems due to its rich mixture to resist mould.

Instructions

Make sure that the area is clean from dust and flaking old walls and ceiling. Do not paint on old flaking plastering and damp walls. For long lasting results, always use Duron Cambond before painting. Apply Duron with roller, paint brush or spray gun and mix paint with 1:10 (one part water and ten parts paint). For long lasting results, it is not recommend to mix with water. Duron paint is recommended for homes and industrial use.

It is important to leave the paint to dry for 1 and half hours before applying another coat.

External Paint application



Duron External paint is available in Smooth and Sandtex finish. Both products come with hardtex material thus resistant for much longer life due to its rich mixture consistency. For long lasting results, always use Duron Cambond before painting.

It is important to leave the paint to dry for 1 and half hours before applying another coat.

Duron Cambond



Cambond is a product that bonds the old paint on walls and ceiling for long lasting bond which gives 100% grip to fresh paint. This product is highly recommended where you have problems with old paint.

Application Instructions:

- Make sure that area is clean from dust and old flaking paint.
- Do not paint on old flaking plastering and damp walls.
- If using plastering, make sure that you'll leave it to dry for at least two days or until completely dry.
- Always use Cambond as an anti-mould solution, before painting and leave it to dry for about two and a half hours or more.
- You can apply Cambond with a paint brush, spray gun or roller.
- Cambond is suitable for both internal and external process.

Keep good ventilation during application. Keep out of reach of children. In case of eye contact, wash immediately with clean fresh water. Remove any traces from skin with soap and water.

Duron Sandtex



Duron Sandtex external paint can be used on all exterior surfaces. It is a top quality, textured exterior finish based on a hardtex acrylic resin, reinforced with silica and micronized granite. Sandtex finish is composed of micronized granite sand; this gives a stronger thicker coating to ordinary exterior paint and offers better protection and weather resistance.

Application process

Make sure that external surfaces are clean and dry. We suggest the use of Duron Cambond as an appropriate primer before painting as this will also act as pre-treatment for mould problems and as a bonding agent of flaking old paint to walls and ceiling. Stir Duron Sandtex well before use.

Apply by brush or roller or spray gun. Ideal for use on any waterproof boards such as Water boards, Cement Board, bricks and limestone walls.

All surfaces must be free of dust & properly prepared. Keep good ventilation during application. Keep out of reach of children. In case of eye contact, wash immediately with clean fresh water. Remove any traces from skin with soap and water.

Duron Liquid Grip



Liquid grip is a product that hardens all the mentioned materials to make them last longer and stronger. Liquid grip can be mixed with all kind of gypsum plaster, plaster products with sand material, tile glue, plaster for joints on stone finishing, silicato, graffiato, polyfiller and lime plaster.

Mix approximately 1180ml of liquid grip with a bag of 20/25Kgs of plaster. Prepare your plaster mixture with water, mix for about 2 min, add liquid grip, and then mix everything for another 2 minutes.

Application of Duron liquid grip on walls before plastering

Before applying the above-mentioned plastering method, you can apply liquid grip directly on the area you will be plastering by mixing 1 part water with 4 parts liquid grip (1:4) on area of approximately 1 m². It is important to follow by rendering straight on it before it gets dry.

Available in 1180ml and 5litres. Keep good ventilation during application. Keep out of reach of children. In case of eye contact, wash immediately with clean fresh water. Remove any traces from skin with soap and water.

Create a perfect colour for your walls.

Over 3,000 of colours are available in 10 litre and 5 litre buckets.